

10/553652

JC09 Rec'd PCT/PTO 14 OCT 2005

INTERNATIONAL PATENT OWNERS (CAYMAN) LIMITED

Complete Substitute Specification
with Amendments

Entitled:

"A support arrangement for use in supporting
a bone during a surgical operation"

**A SUPPORT ARRANGEMENT FOR USE IN SUPPORTING A BONE DURING
A SURGICAL OPERATION**

FIELD OF THE INVENTION

The present invention relates to a support for use in carrying out methods for surgery
procedures and relates in particular to a bone support to assist with method for
removal of unwanted material from within a bone during forms of hip surgery.

The invention It has been developed primarily for removing bonding and other material
from within a femur during hip revision surgery, and it will be described hereinafter with
reference to this application. However, it will be appreciated that the invention is not
limited to this particular field of use and may be adapted to other surgical procedures.

BACKGROUND OF THE INVENTION

Prior art hip replacement surgical techniques typically involve a surgeon firstly
making a ~~fairly~~ large initial incision so as to reveal the hip joint. The surgeon then
typically manipulates the leg of the patient to dislocate the hip bone. This often requires
the application of significant force to effect dislocation. Excessive manipulation and
application of force may cause collateral damage to the patient, possibly resulting in post
operative pain and/or an extended healing time. The head of the femur is then cut off at
the neck. A cavity is reamed into the hip to accept a prosthetic acetabular cup (for
example a LINK T.O.P. Acetabular Cup) and a prosthetic stem (for example a LINK
C.F.P. Hip Stem) is inserted into the femoral shaft. A bonding agent, such as surgical
cement, is typically used to bond the prosthetic acetabular cup into the cavity in the hip
and to bond the prosthetic stem to the femoral shaft. Typically, the surgeon aligns the

cutting and reaming tools by eye, possibly resulting in minor misalignments. Hence, once the prosthetics are installed, there may be visually imperceptible misalignments between the prosthetic acetabular cup and the prosthetic femoral head. This may result in problems such as misalignment of the leg, incorrect leg length and/or incorrect soft tissue tension. Additionally, in the long term, misaligned prosthetic components may wear more quickly, giving rise to aseptic loosening of components and potentially necessitating early repetition of the surgery.

Due to prosthetic component wear over time also giving rise to aseptic loosening of components, many patients require repetition of the surgery. This repetition of surgery, or hip revision surgery, involves replacement of the prosthetic components. It is therefore necessary to remove the worn out components so that they can be replaced with new prosthetics. The removal techniques typically involve a surgeon removing or chipping the old cement away from within the femur and hip of the patient, so that the- new prosthetics can be installed. While the surgeon is removing the old cement, there is a risk that the chipping will cause the bone to collapse outwardly and break. This can result in complications to the surgery. Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of the common general knowledge in the field.

DISCLOSURE OF THE INVENTION

It is an object of the present invention to overcome or ameliorate at least one of the disadvantages of the prior art, or to provide a useful alternative.

It is an object of the present invention in its preferred form to provide a method and apparatus for more safely removing unwanted material from within the femur of a patient during hip -revision or other surgery.

It is also desirable to provide a bone support which facilitates safe removal of cement from a femur which has been subject to a previously implanted prosthesis.

According to one aspect of the invention there is provided a bone support for use in supporting a bone during a surgical operation in which unwanted material is removed from within a cavity of the bone formation, the support including one or more support clamps located by a guide, each support including engagement means to fit around and support said bone during said operation.

~~method of removing unwanted material from within a cavity of a bone during surgery, said method including the steps of:~~

~~a) exposing said bone;~~

~~b) applying at least one support means to said bone to support the structure of said bone; and~~

~~c) removing said material from within said bone cavity.~~

~~According to a second aspect the present invention provides a support arrangement for use in supporting a bone during a surgical operation, the arrangement including one or more supports located by a guide means, each support including means to fit around and support said bone during said operation.~~

Preferably, said support means or support includes a surgical tool guide means to guide a cutting tool for removing said unwanted material.

~~For p~~Preferably, the or each support means or support is a surgical clamp including two arms hingedly connected at or adjacentsubstantially their proximal ends, each of said arms respectively including a respective one of a pair of opposedable bone-supportinggripping formations jaws, at its distal end.

_____. Preferably, the ~~surgical~~support clamp includes an adjustment means for selectively moving said arms into and out of gripping engagement with the bone.

- _____ Preferably, the adjustment means is located at or adjacent said proximal ends of the arms. The adjustment means may include a shaft threadedly engaged through one said arm; a handle located at one end of said shaft; and an abutment portion located at the other end of said shaft such that relative rotation of said handle brings said abutment portion into and out of abutment with the other said arm thereby moving said gripping formations into and out of gripping engagement. The bone-supporting jaws~~gripping formations~~ are preferably concave to fit closely~~snugly~~ around the outer surface of the bone.

Preferably, a plurality of bone supports ~~means~~ are positioned along the bone to fully support it along its length. Desirably, each bone support ~~means~~ is aligned relative to the longitudinal axis of the bone cavity.

For preference, the surgical tool guide means includes a guide rail mounted to at least one of said arms wherein said guide rail is adapted to receive a guide display for displaying the orientation of said bone. Preferably, the guide display is a guide rod slidably mounted to the guide rail. In some embodiments the guide rail is movably mounted to at least one of the arms. In other embodiments the guide rail is fixedly mounted to at least one of the arms.

According to another aspect of the invention there is provided a bone support for use during removal of unwanted material from within a cavity of a bone formation during surgery, said support including a surgical support clamp adapted to engage an external surface of the bone formation, the clamp having a pair of elongated arms with opposed bone-supporting jaws at one end to engage the bone formation, a connecting arrangement by which the arms are connected together and are moveable relative to each other, and an arm moving arrangement associated with the arms by which the opposed jaws are adapted to be urged together to securely grip and support the bone formation.

It will be understood that the bone support of the preferred embodiments acts to limit the likelihood of a bone collapsing outwardly during the process of removing unwanted material from the bone cavity. The support may also assist in maintaining a structurally sound bone formation to receive an implant.

According to ~~another~~^{third} aspect the present invention provides a surgical chisel for use in the method of the first aspect, said chisel including:

a shaft having a hollow portion adjacent a cutting end;

an abutment portion at the other end of said shaft;

the hollow portion having tapering internal walls extending inwardly towards a central axis of the shaft to define a cutting edge at said cutting end.

Preferably, the hollow portion extends along a major portion of the length of said shaft.

For preference, said shaft is generally circular in cross section.

In another aspect, the present invention provides a method of performing hip revision surgery on a patient, said method including the steps of:

- a) exposing a femoral bone formation of said patient;
- b) applying at least one support means as previously described to said femoral bone formation to support the structure of femoral formation;
- and

- c) removing unwanted material from within said femoral bone formation.

Preferably, the method further includes the step of:

- d) extracting a first implant from within said femoral bone formation.

Even more preferably, the method further includes the step of:

inserting a second implant into said femoral bone formation.

Preferably also, the support means is a surgical clamp including two arms hingedly connected at substantially their proximal ends, each of the arms respectively including one of a pair of opposable gripping formations at its distal end.

More preferably step a) includes exposing the femoral bone of the patient through at least two incisions adjacent the bone.

Even more preferably, step b) includes applying the gripping formations to the femoral bone formation through the at least two incisions adjacent the bone.

BRIEF DESCRIPTION OF THE DRAWINGS

A preferred embodiment of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 is a front view of a bone supportsurgical clamp according to a preferred embodiment of the invention shown supporting a femoral bone formation;

Figure 2 is a side view of the surgical clamp shown in Figure 1;

Figure 3 is an enlarged front view of an adjusting formation according to a preferred embodiment of the present invention;

Figure 4 is a side view of the adjusting formation shown in Figure 3;

Figure 5 is an enlarged cut-away view of a guide rail according to a preferred embodiment of the present invention;

Figure 6 is a front view of a surgical cutting tool according to a preferred embodiment of the present invention; and

Figure 7 is a depiction of a femoral shaft illustrating a preferred embodiment of the invention shown supporting the structure of the femoral shaft.

PREFERRED EMBODIMENT OF THE INVENTION

Referring to the drawings, the support ~~means~~ takes in the form of a surgical clamp 1 which includes two elongated arms 2 and 3. The arms 2 and 3 are hingedly connected adjacent ~~at substantially~~ their proximal ends at 4 and 5. Each of the arms 2 and 3 respectively includes a respective one of a pair of ~~opposedable~~ bone-supporting, gripping formations, or jaws, 6 and 7 at ~~the~~ its distal end 8. In this embodiment, the gripping formations, or jaws, 6 and 7, are concave, However, in other embodiments, the

gripping formations may take other shapes. For example, in one preferred embodiment,
they jaws are substantially flat. The jaws 6 and 7 have a lateral extent, relative to the
arms 2 and 3, so as to engage a substantial portion of and along the length of the bone
formation 11 to which the support is fitted to thereby support that portion, at least,
against outward collapse.

-The surgical clamp 1 includes an adjusting ~~mechanism~~ formation 9 for selectively
moving the arms 2 and 3 into and out of gripping engagement with ~~an~~ the outer surface 10
of ~~the~~ a femoral bone formation 11. The adjusting ~~mechanism~~ 9formation includes a
threaded shaft 12 threadedly engaged through one of the arms 3. A handle 13 is located
at one end 14 of the shaft 12 and an abutment portion 15 is located at the other end 16 of
the shaft. Relative rotation of the handle 13 selectively ~~moves~~ brings the abutment portion
15 into ~~and out of abutment engagement~~ engagement with the other arm 2, to thereby moving the
jaws ~~gripping formations 6 and 7 into and out of gripping engagement with the femoral~~
bone formation 11.

-A surgical tool guide means, in the form of a guide rail 17, is either fixedly or adjustably
mounted to arm 3 to guide a cutting tool for removing unwanted material such as glue or
cement from within the femoral bone formation 11. The guide rail 17 is adapted to
receive a guide display, in the form of a guide rod 19 (Figure 7), which is slidably
mounted to the guide rail 17 for displaying the orientation of the femoral bone formation
11 relative to one or more bone supports 1.

Referring to Figure 6 there is shown a cutting tool in the form of surgical chisel 20. The
chisel 20 includes a hollow shaft 21 and an abutment portion 22 at one end 23 of the
shaft. A cutting end 24 is provided at the other end of the shaft 21. The cutting end has
inwardly tapering walls 25 and 26 which define a cutting edge 27.

Referring to Figure 7, in use, a number of the clamps 1 are inserted by the surgeon
through incisions adjacent the femoral bone 11 of the patient and positioned with the

~~bone-supportinggripping-formations~~ jaws 6 and 7 around the surface bone formation 11 over a portion of its length. In this embodiment each ~~pair of jaws~~gripping formation 6 and 7 is applied to the bone formation 11 through separate respective incisions (not shown). The respective arms 2 and 3 of each of the supports which extend outside the patient are then adjusted by the respective handles 13 to bring the ~~formations~~opposed jaws 6 and 7 into supporting engagement with the bone formation 11 along a portion of the length of the bone formation 11. Each ~~support~~clamp is aligned relative~~respective~~ to each other and to the bone formation 11 by the guide rail 17. As each clamp is of the same length, the guide rail 17 extends generally parallel to and provides a guide as to the longitudinal axis of the bone formation. The rod 19 attached to the guide rail 17 can thus be used to indicate to the surgeon the position of the bone formation and to assist in guiding a surgical tool used for cleaning out the cavity of the bone formation. Once the bone is fully supported by the bone-supporting jaws 6 and 7~~clamps~~, the surgeon can commence ~~chiselling~~-removal of cement or other unwanted material from the cavity of the bone formation 11 by using the chisel 20. It will be appreciated that some implants are not cemented or bonded into place and that the preferred embodiment of the invention may be used in either of those situations. The configuration of the chisel 20 allows waste material to be captured and withdrawn by means of the hollow shaft ~~portion~~ 21. Some examples of waste material include existing waste particles, elements of chronic inflammation and generated waste particles. The chisel is typically dimensioned so as to fit neatly within the bone cavity and allow alignment with the guide rod 19. It will be apparent to those in the art that a variety of other means can be used to remove unwanted material from the bone cavity provided the bone is adequately supported during removal.

While in ~~some~~the preferred embodiments the guide rail 17 is fixedly mounted to arm 3, in other embodiments it is movably mounted to the arm. For example, when used in the

configuration as shown in Figure 7, the outer surgical clamps 28 may have guide rails that are fixedly mounted, while the inner clamps 29 may have guide rails that are movably mounted. This is beneficial as in some instances the femoral bone formation 11 may have an outer edge which deviates from straight and if one of the clamps is applied to such a deviation, this may cause the guide rails 17 to misalign. Therefore if the one of the inner clamps 29 is applied to such a deviation, having a movable guide rail 17 facilitates the insertion of the guide rod 19.

In situations where the hip or other implant is not cemented in place, it may not be possible to remove the implant prior to application of the supportclamps 1 as described above. In such a case the supportclamps 1 are firstly applied to supporthold the bone and are used as a guide while removing the implant.

It will be appreciated that the preferred embodiment and/or modified versions of the preferred embodiment can be applied to the insertion and extraction of a wide variety of implants and its uses are not limited to hip revision surgery. For example, a preferred embodiment of the present invention is adapted for use in the methods and with the apparatus disclosed in co-pending patent application no. PCT/AU02/01482 (WO 03/037192), the contents of which are hereby incorporated in their entirety by way of reference.